

8900 Series 1080P 5in1 DVR



Features :

- Support VGA and HDMI full HD output simultaneously
- Support ONVIF
- Support AHD, CVI, TVI, CVBS, IP video input
- Support 4MP HD camera, 720P/1080P realtime, recording and playback
- Transmission over long distances up to 500 meter HD video signals
- Support mouse, apply a new GUI, more intuitive and simple user experience using the menu style display
- Remote Monitoring : Support P2P, Web Server, CMS

8900 Series 1080P 5in1 DVR

Specification :

| 1080P 4.0MP DVR | | | |
|-------------------------------|------------------------|---|---|
| System | Main Board | Industrial Embedded Microprocessor, Hi3520DV300 | |
| | Operating System | Embedded LINUX operating system | |
| | Channel | 4 / 8 / 16 Channel | |
| | Video Coding | H.264 | |
| | Resolution | Support 960H / 720P / 1080P / 4MP | |
| | Multi Mode Video Input | DVR Mode | 4MP*Ch |
| | | HVR Mode | 4MP*Ch + 4MP(IPC)*Ch |
| | | NVR Mode | 1080P*16Ch / 1080P*9Ch / 960P*16Ch / 5M*4Ch |
| | Video Frame | PAL / NTSC (1080P) Selectable | |
| Audio Coding | G.711 | | |
| Video Spec | Video Input | 4 / 8 / 16CH BNC Port | |
| | Video Output | VGA x 1, HDMI x 1 | |
| Audio Ports | Audio Input / Output | 2CH RCA Audio Input / 1CH RCA Audio Output | |
| Recording | Recording Mode | Auto Recording, Manual Recording, Motion Detection Recording | |
| | Playback | 720p @25fps | |
| | | 1080P @25fps | |
| | HDD Space Occupation | Video : 1080P 48G/day x channel; 720P 20G/day x channel; 960H 12 ~ 20G/day x channel; | |
| Audio: 691.2M / day x channel | | | |
| Backup Mode | Hard Disk / Network | | |
| Network | Protocol | Support TCP/IP, UDP, RTP/RTSP, DHCP, DDNS, NTP, FTP etc | |
| | IE Control | with WEB SERVER to modify configuration parameters and remote control IE | |
| | Mobile Remote | Support IOS, Android (XMEYE) | |
| | P2P Cloud | Yes, support login via www.xmeye.net to meet remote viewing and control | |
| HDD | HDD Port | 2 x 6TB SATA HDD, e-SATA Port not support | |
| Interface | Network / USB | 1 x RJ45 10/100M Ethernet Port; 2 x USB Port | |
| | Interface | 1 x Standard RS485 Port | |
| Others | Power Input | DC12V 4A <15W Not including HDD | |
| | Temperature / Humidity | Temperature : -10°C ~ 55°C / Humidity : 10% ~ 90% | |