



ELOCK AL3000 is a streamlining platform for intelligent security system, permitting all around 24/7 protection to your family. It embedded the tone or voice feedback, call in/out functions.

Moreover, the system offer GSM & zone expansion module as add on feature. Hence, customer will enjoy a low start up cost.

Product Features :

- (1) **9 Zone Alarm**
8 zone with EOL on board, expandable up to 16 zone. Zone 9 for panic button, remote control arm/disarm with siren/strobe light indication.
- (2) **Maximum up to 4 Keypad**
Each keypad have own ID address.
- (3) **CMS and Personal Call Reporting**
CMS Reporting x 2 and Personal Call Reporting x 4
- (4) **Access Code**
Master code x 1 + User code x 8 + Installer code x 1
- (5) **Auto Arm / Disarm**
Permitting the arm/disarm function at the preset time.
- (6) **Monitoring of Telephony Line**
Provide the warning upon the telephony line is being tampered.
- (7) **CMS Reporting** (Contact ID)
Provide the connection to control monitoring station at ease.
- (8) **Control via Local Keypad or Smartphone Devices**
Provide the convenience to user anytime and anywhere
- (9) **Optional Upgrade to GSM for SMS Reporting**
Reporting via GSM line and SMS reporting on power failure, arm/disarm, battery low, system trouble and alarm.

Technical Information :

Power Supply	240VAC input (14VAC, 3A Customized Transformer by ELOCK)
Standby Current	Max 100mA
Backup Battery	12VDC, 7AH Rechargeable Battery
Siren, Strobe Light Power Output	Max 2A (12VDC)
Auxillary Power Output	Max 1A (12VDC)
Keypad Power Output	Max 1A (12VDC)
Keypad Dimension	(L) 115mm x (W) 80mm x (H) 22mm
Metal Casing	(L) 290mm x (W) 300mm x (H) 80mm
System Reset Button	Mainboard System Restart
Communication Format	Contact ID (CMS)
Dedicated Input	Remote Arming and Disarming

9 Zone Tone System Wiring Diagram (TONE)

Your Security is Our Responsibility
eLock
www.elock2u.net

