

Overview

EL-DH-604 is a wall mount door holder which adopts low power consumption that makes it more environments friendly and more durable. It will release automatically the fire door in case of fire. It also contains build-out release button for testing and build-in MOV which reverse current protection.


Specification


Product Parameter	Parameter Description
Dimensions	70L x 40W x 85H (mm)
Holding Force	50kg (110Lbs)
Voltage	12/24VDC +/- 10%
Current Draw	12V/180mA 24V/70mA
Suitable for	All kind of Single & Double
	Smokeproof Doors
Surface Temp	≤ +20 °C
Operating Temp	-10∼+55°C(14-131F)
Suitable Humidity	0~90%(relative humidity)
Finishes for Shell	High Temperature Paint and
	Environmental Protection
	Zinc
Finishes for Armature	Zinc
Weight	0.9kg




FAX +603-8051 4919 WEB www.elock2u.net EMAIL enquiry@elock2u.net

Dimensions





Installation



Circuit Board Instruction

EMAIL



Kyodensha Technologies (M) Sdn Bhd (2057536-M) Digit Innovation Technologies (M) Sdn Bhd (646972-U)

No. 12A Jalan PPU3A, Pusat Teknologi Sinar Puchong 47150 Puchong Selangor, Malaysia TEL +603-8066 4636 +6038051 5788 FAX +603-8051 4919 WEB www.elock2u.net

enquiry@elock2u.net