

DOOR CONTACT SERIES

EL-800S SHOCK SENSOR



Sensitivity:	Adjustable (High To Low)
Contact Type:	N.C
Response Time:	Instant
Material:	Gold Plated Contact
Mounting Type:	Surface Mount
Dimension:	60 (L) x 22 (D) x 22 (W) mm

EL-800P 1" DOOR CONTACT



Contact Rating:	0.5A @100V DC /10W max
Working Distance:	1" (25.4 mm) with Rare Earth Magnet
Operating Gap:	not less than 1/4" (6.35mm)
Contact Type:	N.C/ COM
Mounting Type:	Surface Mount
Material:	Ruthenium Over Gold Reeds
Wiring Type:	2- wire
IP Rating:	IP65 (Weatherproof)
Color Options:	White, Brown
Dimension:	33 (L) x 8 (D) x 15 (W) mm

EL-810P 1 1/4" DOOR CONTACT



Contact Rating:	0.5A @100V DC /10W max
Working Distance:	1 1/4" (31 mm) with Rare Earth Magnet
Operating Gap:	not less than 1/4" (6.35mm)
Contact Type:	N.C/ COM
Mounting Type:	Surface Mount
Material:	Ruthenium Over Gold Reeds
Wiring Type:	2- wire
IP Rating:	IP65 (Weatherproof)
Dimension:	33 (L) x 8 (D) x 15 (W) mm

DOOR CONTACT SERIES

**EL-820P METAL
DOOR CONTACT**



Contact Rating:	0.5A @100V DC /10W max
Working Distance:	1 1/2" (38 mm) with Rare Earth Magnet
Operating Gap:	not less than 1/4" (6.35mm)
Contact Type:	N.C/ COM
Mounting Type:	Surface Mount
Material:	Ruthenium Over Gold Reeds
Wiring Type:	2- wire
IP Rating:	IP65 (Weatherproof)
Dimension:	33 (L) x 8 (D) x 15 (W) mm

**EL-830P PRESS
DOOR CONTACT**



Contact Rating:	0.5A @100V DC /10W max
Working Distance:	3/4" (20 mm) with Rare Earth Magnet
Operating Gap:	not less than 1/4" (6.35mm)
Contact Type:	N.C/ COM
Mounting Type:	Flush Mount
Material:	Ruthenium Over Gold Reeds
Wiring Type:	2- wire
IP Rating:	IP65 (Weatherproof)
Color Options:	White, Brown
Dimension:	33 (L) x 8 (D) x 15 (W) mm

**EL-840P PRESS FIT
DOOR CONTACT**



Contact Rating:	0.5A @100V DC /10W max
Working Distance:	1 1/2" (38 mm) with Rare Earth Magnet
Operating Gap:	not less than 1/4" (6.35mm)
Contact Type:	N.C/ COM
Mounting Type:	Flush Mount
Material:	Ruthenium Over Gold Reeds
Wiring Type:	2- wire
IP Rating:	IP65 (Weatherproof)
Color Options:	White, Brown
Dimension:	33 (L) x 8 (D) x 15 (W) mm