

## EXIT BUTTON SERIES

EL-PT4510 WATERPROOF  
TOUCH EXIT BUTTON



Power Supply:	DC12V / DC24V
Contact Type:	N.O/ N.C/ COM
Frequency:	433.92 MHZ
Material:	Aluminium Frame+ Tempered Glass Panel
IP Rating:	IP67 ( Dust Tight & Waterproof 1m)
Mechanical Life:	1,000,000 Aging Test Qualified
LED Effect:	Static Light Effect
Dimension:	115 (H) x 10 (D) x 45 (W) mm

EL-PT8610 WATERPROOF  
TOUCH EXIT BUTTON



Power Supply:	DC12V / DC24V
Contact Type:	N.O/ N.C/ COM
Frequency:	433.92 MHZ
Material:	Aluminium Frame+ Tempered Glass Panel
IP Rating:	IP67 ( Dust Tight & Waterproof 1m)
Mechanical Life:	1,000,000 Aging Test Qualified
LED Effect:	Static Light Effect
Dimension:	86 (H) x 10 (D) x 86 (W) mm

EL-NT4510 WATERPROOF  
TOUCHLESS EXIT BUTTON



Power Supply:	DC12V / DC24V
Contact Type:	N.O/ N.C/ COM
Frequency:	433.92 MHZ
Material:	Aluminium Frame+ Tempered Glass Panel
IP Rating:	IP67 ( Dust Tight & Waterproof 1m)
Mechanical Life:	1,000,000 Aging Test Qualified
LED Effect:	Breathing Light Effect
Dimension:	115 (H) x 10 (D) x 45 (W) mm

EL-NT8610 WATERPROOF  
TOUCHLESS EXIT BUTTON



Power Supply:	DC12V / DC24V
Contact Type:	N.O/ N.C/ COM
Frequency:	433.92 MHZ
Material:	Aluminium Frame+ Tempered Glass Panel
IP Rating:	IP67 ( Dust Tight & Waterproof 1m)
Mechanical Life:	1,000,000 Aging Test Qualified
LED Effect:	Breathing Light Effect
Dimension:	86 (H) x 10 (D) x 86 (W) mm

**EL-PT4510RC WATERPROOF TOUCH EXIT BUTTON WITH RECEIVER & REMOTE**



Power Supply	DC12V / DC24V
Contact Type:	N.O/ N.C/ COM
Frequency:	433.92 MHZ
Material:	Aluminium Frame+ Tempered Glass Panel
Delay Timer:	5/10/20/30 secs
Optional Remote Distance:	Up to 300 meters
User Capacity:	30 Remotes
Self-Locking Function:	Available
IP Rating:	IP67 ( Dust Tight & Waterproof 1m)
Mechanical Life:	1,000,000 Tested Aging Test Qualified
LED:	Static Light Effect
Dimension:	Exit Button: 115 (H) x 10 (D) x 45 (W) mm ; Receiver: 64(H) x 20 (D) x 25 (W) mm

**EL-EB1W WATERPROOF PRESS EXIT BUTTON**



Contact Rating :	8A @125V AC / 5A@250V AC max
Contact Type:	N.O/ COM
Material:	304 Stainless Steel Panel
IP Rating:	IP67 ( Dust Tight & Waterproof 1m)
Mechanical Life:	500,000 Aging Test Qualified
Dimension:	100 (H) x 26.5 (D) x 35 (W) mm
Available in:	IP65 EL-EB1 (4A @125V AC / 2A@250V AC max)

**EL-EB3W WATERPROOF PRESS EXIT BUTTON**



Contact Rating :	8A @125V AC / 5A@250V AC max
Contact Type:	N.O/ COM
Material:	304 Stainless Steel Panel
IP Rating:	IP67 ( Dust Tight & Waterproof 1m)
Mechanical Life:	500,000 Aging Test Qualified
Dimension:	87 (H) x 22 (D) x 87 (W) mm
Available in:	IP65 EL-EB3 (4A @125V AC / 2A@ 250V AC max)

EL-EC1 TOUCH EXIT BUTTON



Power Supply :	DC12V / DC24V
Contact Type:	N.O/ N.C/ COM
Material:	304 Stainless Steel Panel
IP Rating:	IP40 (Dry Indoor)
Mechanical Life:	100,000 Aging Test Qualified
LED:	Static
Dimension:	86 (H) x 20 (D) x 50 (W) mm

EL-EC2 TOUCH EXIT BUTTON



Power Supply :	DC12V / DC24V
Contact Type:	N.O/ N.C/ COM
Material:	304 Stainless Steel Panel
IP Rating:	IP40 (Dry Indoor)
Mechanical Life:	100,000 Aging Test Qualified
LED:	Static
Dimension:	86 (H) x 20 (D) x 86 (W) mm

EL-S886M5 WATERPROOF MUSHROOM EXIT BUTTON



Contact Rating :	3A @ 36VDC Max
Contact Type:	N.O/ N.C/ COM
Frequency:	433.92 MHZ
Material:	Stainless Steel Panel+ Plastic Button
IP Rating:	IP68 ( Dust Tight & Waterproof 3m)
Mechanical Life:	1,000,000 Aging Test Qualified
Operating Temperature:	-20°C to +55°C
Dimension:	86 (H) x 20 (D) x 86 (W) mm
Available In:	Red & Green

EL-WLPB1 WIRELESS PUSH EXIT BUTTON



Battery:	27A @ 12V x 1pc
Frequency:	433.92 MHz
Material:	ABS Plastic
IP Rating:	IP40 (Dry Indoor)
Dimension:	86 (H) x 10 (D) x 86 (W) mm

## EXIT BUTTON SERIES

---

EL-SB1A PUSH EXIT BUTTON



Contact Rating :	4A @125V DC max / 2A@250V AC
Contact Type:	N.O/ COM
Material:	ABS Plastic
IP Rating:	IP40 (Dry Indoor)
Dimension:	86 (H) x 20 (D) x 86 (W) mm

EL-EB5 & EL-EB5A  
EMERGENCY/EXIT PUSH BUTTON



Contact Rating :	0.5A @24V DC max
Contact Type:	Momentary
Material:	ABS Plastic
IP Rating:	IP40 (Dry Indoor)
Dimension:	76 (H) x 15 (D) x 23 (W) mm
Available In:	EB5 Exit, EB5A Emergency