

## KEY SWITCH SERIES

EL-KS1 KEY SWITCH



Contact Type:	SPST (NO+COM/ NC+COM )
Number of Positions:	2 (On/ Off)
Contact Rating:	4A @125V AC/ 2A @250V AC max
Door Status Sensor:	1NO+1NC
Mounting Type:	Flush Mount, Panel Mount
Material:	Stainless Steel Panel
IP Rating:	IP44 (Splash Resistant)
Dimension:	87 (H) x 23 (D) x 87 (W) mm

EL-KS2 NARROW TYPE KEY SWITCH



Contact Type:	SPDT (NO/NC/COM)
Number of Positions:	2 (On/ Off)
Contact Rating:	4A @125V AC/ 2A @250V AC max
Door Status Sensor:	1NO+1NC
Mounting Type:	Flush Mount, Panel Mount
Material:	Stainless Steel Panel
IP Rating:	IP44 (Splash Resistant)
Dimension:	100 (H) x 23 (D) x 35 (W) mm

EL-KS3L LED DOOR RELEASE KEY SWITCH



Contact Type:	SPDT (NO/NC/COM/TAMP)
Number of Positions:	2 (On/ Off)
Contact Rating:	3A @36V DC max
Door Status Sensor:	1NO+1NC
LED:	Available
Mounting Type:	Flush Mount, Panel Mount
Material:	Stainless Steel Panel
IP Rating:	IP44 (Splash Resistant)
Dimension:	86 (H) x 20 (D) x 86 (W) mm