

BT100 BACKUP BATTERY



Nominal Voltage:	12V
Rated Capacity (20 Hour Rate) :	7Ah
Cells Per Battery:	6
Lifespan:	10 Years Floating Design Life at 25°c
Internal Resistance:	Full charged at 25°C(77°F): Approx 28mΩ
Max.Discharge Current:	70A (5Sec.)
Weight:	2kg (4.41lbs) ± 3%
Standards:	IEC, BS, JIS, Eurobat Standards & CE Approved
Dimension:	151 (L) x 65 (W) x 94 (H) mm

KY100 12V 3A
POWER SUPPLY



Input Voltage:	220 ~ 240 VAC
Input Frequency:	50~60 Hz
Output No Load Voltage:	13.5 VDC
Output Rated Voltage:	13.0 VDC
Output Rated Current:	3.0 A DC
Load Regulation:	NL to FL3%
Battery Low Cut-off:	10.5 VDC
Operating Temperature:	0 ~ 65° C
Casing Surface Finishing:	Oven baked epoxy powder coating
Dimension:	245 (W) x 255 (H) x 88 (D)mm

KY150 12V 5A
POWER SUPPLY



Input Voltage:	220 ~ 240 VAC
Input Frequency:	50~60 Hz
Output No Load Voltage:	13.5 VDC
Output Rated Voltage:	13.0 VDC
Output Rated Current:	5.0 A DC
Load Regulation:	NL to FL3%
Battery Low Cut-off:	10.5 VDC
Operating Temperature:	0 ~ 65° C
Casing Surface Finishing:	Oven baked epoxy powder coating
Dimension:	245 (W) x 255 (H) x 88 (D)mm

PS-RS5012 12V 4.2A
SWITCHING POWER SUPPLY



Input Voltage:	220 ~ 240 VAC
Input Frequency:	50~60 Hz
Output Rated Voltage:	12.0 VDC
Output Rated Current:	4.2 A DC
Power Indicator	LED For Power On
Components:	105° C Long Life Electrolytic Capacitors
Surge Protection:	Withstands 300VAC surge input for 5 secs
Operating Temperature:	0 ~ 70° C
Power Consumption(No Load):	<0.5W
Dimension:	245 (W) x 255 (H) x 88 (D)mm
Available In:	PS-RS5024 I/P:240 VAC, O/P:24 VDC (2.2A)

PS-SE10012 12V 8.5A
SWITCHING POWER SUPPLY



Input Voltage:	220 ~ 240 VAC
Input Frequency:	50~60 Hz
Output Rated Voltage:	12.0 VDC
Output Rated Current:	8.5 A DC
Power Indicator	LED For Power On
Components:	105° C Long Life Electrolytic Capacitors
Surge Protection:	Withstands 300VAC surge input for 5 secs
Operating Temperature:	0 ~ 70° C
Power Consumption(No Load):	<0.5W
Dimension:	245 (W) x 255 (H) x 88 (D)mm

EL-AD100R REGULATED
POWER ADAPTER



Input Voltage:	220 ~ 240 VAC
Input Frequency:	50~60 Hz
Output Rated Voltage:	12 VDC
Output Rated Current:	1.0 A DC
Operating Temperature:	0 ~ 65° C
Polarization:	Positive Center
Type:	AC/DC Wall-Mounted Adapter
Cord Plug Length:	1.8 m length with 2.1 mm I.D. x 5.5 mm O.D., 12 mm Female Pin
Plug Type:	UK Plug Type
Dimension:	81 (W) x 55(H) x 56 (D)mm